

A. Title of the invention: PROCESS AND DEVICE FOR SEALING OR REDUCING
HOLES, AND CONNECTING HOLES WITH A TUBE END.

B. Cross-reference to related applications.

5 C. Background of the invention.

1. Field of the invention.

The presented invention concerns a method and device for sealing or reducing drilled
holes or their connection with a tube end or similar connections.

10 2. Description of related art including information disclosed under 37 CFR 1.97 and
37 CFR 1.98.

In practically all technical areas there is a necessity to seal drilled holes such that they are
leak-free, e.g. an auxiliary drill hole in the hydraulic or pneumatic branch, or to reduce diameter
of the drilled hole for adjusting to new requirements or to connect a drilled hole to a tube end,
15 without having to utilize techniques such as threading, which are susceptible to leakage or which
are labor intensive and expensive such as welding or soldering techniques. The latter techniques
are often not possible due to the necessary generation of heat.

In a known technique, a drilled hole, e.g. an auxiliary drill hole in the hydraulic- or
pneumatic branch, to be sealed without leakage, a stopper cup is inserted into the hole and is
20 expanded by pressing a ball into the open end of the cup. Thus, the cup is radially expanded to
press into the wall of the hole thus sealing the hole. In order to reduce a drilled hole by the same
method, instead of the stopper cup, closed at the front end, a piece of tubing may be used, and in

EXPRESS MAIL LABEL NUMBER ~~EK60081242545~~

EK60081239945

order to connect the respective drill hole to a tube end, this tube itself has to be expanded into the drill hole.

This technique is expensive, requiring extensive and precise machining, and requires for a leak free press fit of the tubing material at the drill hole walls, a substantial drilling depth and close concentricity between the wall of hole wall and the opposing surface of the device.

D. Brief summary of the invention.

The method of the present invention achieves the leak tight seal by axial pressure, possibly with an additional tumbling action. At least one element is inserted into the hole to be sealed, and is at least temporarily supported by a support shoulder or other means. The element has the shape of a disc, which has been formed into a conical or domed shape such that axial pressure tending to flatten or collapse the element causes a radial expansion of the rim of the disc shaped surface to achieve a press fit with the wall of the drilled hole. The element may be formed of a flat disc, washer, or other flat piece having an annular rim, the piece being formed into the element of the present invention in the desired conical shape by placement in a conical die and impacted by a ball or other tool to form the desired cone or dome shape. The shaping process acts to reduce the diameter of the element rim such that the rim will radially expand, returning toward its original diameter when flattened by axial pressure exerted against the apex of the conical shape when opposed by axial force or restraint of the rim. The opposing axial force exerted against the rim may be supplied by a support shoulder, or by an opposing tool.

In a further development of the invention, in a device of the present invention, the element can be configured as a perforated disc or a disc with a center hole, or as a tube section or a threaded bolt with a flange which forms the disc shape surface with cone or dome shaped configuration.

In another development of the device of the present invention the element can show a cone or dome shaped configuration circumferentially close to the rim, whereby an annulus of material is projected above the surface of the element, with a outer frusta-conical surface and an inverted frusta-conical inner surface. The method of the present invention may be further applied to configure the flanged end of a tube as the conical element, which, when flattened by axial force on the tube and axial restraint of the flange rim, will radially expand the flange rim into a press fit. This result can also be achieved using a conically shaped, perforated disc for a connection with a tube end, whereby, under pressure, a radial expansion and a press fit of the rim of the disc is achieved with the wall of the hole and of the edge of the perforation of the disc with the cylindrical wall of the tube end.

In yet a further development of the device of the present invention the element can be a a folded annulus having two frusta-conical surfaces inverted with respect to each other and formed of one piece, such that axial pressure applied to top and bottom rims in opposing directions will flatten and radially expand the element. An elastomeric material may be retained axially between the opposing surfaces and squeezed into sealing contact with the hole wall when the element is flattened.

The principal aim of the present invention is to provide a new and improved method and devise for sealing or reducing a hole or connecting a component which meets the foregoing requirements and which is capable of being easily installed in a hole or bore.

Another and further object and aim of the present invention is to provide a new and improved method and devise for sealing or reducing a hole or connecting a component which meets the foregoing requirements and which is economical to manufacture and to provide an economical method of manufacture and installation.

Yet another and further object and aim of the present invention is to provide a new and improved method and devise for sealing or reducing a hole or connecting a component which meets the foregoing requirements and which can be installed in either direction.

Other objects and advantages of the invention will become apparent from the Description of the Preferred Embodiments and the Drawings and will be in part pointed out in more detail hereinafter. The invention consists in the features of construction, combination of elements and arrangement of parts exemplified in the construction hereinafter described and the scope of the invention will be indicated in the appended claims.

G. Brief description of the several views of the drawing.

FIG. 1 is a cross section view of a preferred embodiment of a device constructed in accordance with the present invention placed in a circular hole, but not fully installed therein.

FIG. 2 comprises two cross section views of another preferred embodiment of a device constructed in accordance with the present invention, which, on the left hand has been placed in a circular hole, but not fully installed therein, and on the right hand has been fully installed.

FIG. 3 is a cross section view of another preferred embodiment of a device constructed in accordance with the present invention placed in a circular hole, but not fully installed therein.

FIG. 4 is a split cross section view of another preferred embodiment of a device constructed in accordance with the present invention, which, on the left hand has been placed in a circular hole, but not fully installed therein, and on the right hand has been fully installed.

FIG. 5 is a split cross section view of another preferred embodiment of a device constructed in accordance with the present invention, which, on the left hand has been placed in a circular hole, but not fully installed therein, and on the right hand has been fully installed.

FIG. 6 is a cross section view of another preferred embodiment of a device constructed in accordance with the present invention placed in a circular hole, but not fully installed therein.

FIG. 7 comprises two cross section views of another preferred embodiment of a device constructed in accordance with the present invention, which, on the left hand has been placed in a circular hole, but not fully installed therein, and on the right hand has been fully installed.

FIG. 8 is a split cross section view of another preferred embodiment of a device constructed in accordance with the present invention, which, on the left hand has been placed in a circular hole, but not fully installed therein, and on the right hand has been fully installed.

H. Detailed description of the invention.

The Drawings show a variety of configurations of devices constructed in accord with the present invention, all of which have in common a round disc shaped element configured with a conical, frusta-conical or dome shaped surface, which elements are designated by the numeral 4 in Figs 1 and 2, by the numeral 4' in Fig. 3, by the numeral 4'' in Figs 4 and 7, by the numeral 4''' in Fig. 6, and by the numeral 4'''' in Fig. 8. The present invention being directed to sealing, reducing or securing a tube to a hole in a boss, the drawings are oriented such that the top of the drawings correspond to the outside of the hole and the bottom corresponds to the inside of the hole, and directions such as up, top, down or bottom derive their meaning accordingly. In the drawings, the general point of application, and direction of axial pressure is indicated by the arrows designated by the numeral 6, and the arrows designated by the numeral 6' indicate the direction of radial expansion of the rim of the device.

Fig. 1 shows a round disc shaped element 4 of the device per invention manufactured from steel or similar material in a round drill hole 1 with inner support shoulder 2 in a metallic body 3, e.g. an engine block, to seal the drill hole 1. The element 4 in this case is smaller in diameter than the diameter of the drill hole 1 and of dome shaped configuration. Arrows 6' show the direction of the radial shift and press fit of the rim zone 5 of the disc shaped element 4 with the wall of the drill hole 1 upon application of an axial pressure on the disc shaped element 4 as shown by arrow 6. Said axial pressure is exerted by a suitable punch (not shown), perhaps with an additional tumbling action. If in such a configuration the named support shoulder 2 is missing, at least the rim 5 of the element 4 has to be at least temporarily supported, e.g. by a suitable counter punch (not shown).

A further variation of the configuration is shown in Fig. 7 whereby for connecting the drill hole 1 with a tube end 11, e.g. a tube nipple, the element 4'' of the device of the present invention has a central perforation similar to that shown in Fig. 4, and can be used either singly or plurally as shown in the arrangement in Fig. 2. Under axial pressure, a radial shift and press fit of the rim zone of the disc shaped surface with the wall of the installation hole is achieved, as is a press fit of the hole edge of the disc shaped surface with the cylinder wall of the tube end 11.

Furthermore the element 4''' of the device per invention may be a perforated disc per Fig. 8 with a cone or dome shaped circumferential rim zone 12. Element 4''' is formed of an annular piece comprising two coaxial frusta-conical surfaces, the bases of which correspond to the rim zone, and contact the hole wall, the bottom surface angling inwardly upward and the top surface angling inwardly downward. A gap exists between the two surfaces before installation, which gap may receive an elastomeric seal material. Upon application of axial pressure according to arrow 6, the two surfaces flatten and the rims thereof approach each other while radially expanding to a press fit in the hole.

The method of the present invention comprises the sealing, reducing, or connecting a component to an installation hole by forming a device with a conical or dome shaped element with a radially outer rim, and at least temporarily supporting at least said rim by a support shoulder or other means, and applying axial pressure to the element in opposition to the rim support, possibly with an additional tumbling action. The element has the shape of a disc, which has been formed into a conical or domed shape such that the axial pressure tends to flatten or collapse the element causing a radial expansion of the rim, thereby achieving a press fit with the wall of the installation hole. The element may be formed of a flat disc, washer, or other flat piece having an annular rim, the piece being formed into the conical or frusta-conical element of

the present invention in the desired conical shape by placement in a conical die and impaction by a ball or other tool to form the desired cone or dome shape. The insertion of a tube or other component into a central opening in the element can achieve a press fit of the tube within the element. While the drawings and description uniformly describe the axial pressure exerted from above upon the peak or apex of the conical element with opposing force supporting the rim exerted upward, it will be anticipated that the direction and area of application of these forces could be reversed so long as the forces are opposing.

While preferred embodiments of the foregoing invention have been set forth for purposes of illustration, the foregoing description should not be deemed a limitation of the invention herein. Accordingly, various modifications, adaptations and alternatives may occur to one skilled in the art without departing from the spirit and the scope of the present invention.